

SureBead® self-cleaning hot melt dispensing applicators

Non-clogging hot melt guns deliver cleaner operation and less maintenance and downtime



Features

Nordson SureBead applicators set the industry standard for trouble-free performance, delivering more uptime and productivity to your operations.

- Self-cleaning, integrated needle and reduced cavity nozzle design*
- Removable Saturn® style nozzles with color-coded rings
- Myritex™ long-life seals
- Easy-On™ Bowtie® one-way-fit mounting design
- Color-coded, cool-to-touch module covers
- Fully rebuildable gun modules

Benefits

- Clog-free operation minimizes downtime, maintenance, replacement and inventory costs
- Error-free nozzle and bead size changes without removing gun module
- Unique seals extend module service life
- Guided, one-way fit for fast, easy installation increases uptime
- Less operator exposure to heated surfaces improves safety
- Rebuild kits lower replacement parts costs

**Patented*



SureBead® self-cleaning hot melt dispensing applicators

Specifications

Operating Temperature	450° F (230° C) maximum
Operating Air Pressure ¹	45 to 80 psi (3.1 to 5.5 bar)
Working Hydraulic Pressure	1500 psi (103 bar) maximum
Operating Speed	Exceeds 3500 cycles per minute
Precision Nozzles ²	Single; selected nozzle comes mounted on module
Saturn® Solenoid Valves ³	Nordson 24 VDC Saturn high-temperature solenoids recommended for peak performance
Electrical Service	240 VAC, 50/60 Hz 200 VAC, 50/60 Hz optional

Notes:


1. Recommended range. Dry, regulated, unlubricated air required for consistent gun operation.
2. Optional SureBead nozzle/orifice diameters and centerline spacings are available.
3. Nordson specifies 24 VDC Saturn high-temperature valves for pattern accuracy and extended service life.



Color-coded plastic module covers provide easy identification of AO/AC (blue) or AO/SC (black) characteristics; brown color indicates needle/seal design.



Removable, reduced cavity nozzle allows fast bead size changes without removing the module



Self-cleaning, non-clogging SureBead module with needle and seat design and integrated Saturn reduced cavity nozzle

For more information, speak with your Nordson representative or contact your Nordson regional office.

United States

Duluth, Georgia
(800) 683-2314 **Phone**
(866) 667-3329 **Fax**

Canada

Markham, Ontario
(800) 463-3200 **Phone**
(905) 475-8821 **Fax**

Europe

Erkrath, Germany
(49) 211-9205-0 **Phone**
(49) 211-254658 **Fax**

Japan

Tokyo, Japan
(81) 3-5762-2700 **Phone**
(81) 3-5762-2701 **Fax**

Asia/Australia/

Latin America
Amherst, Ohio
(440) 985-4797 **Phone**
(440) 985-1096 **Fax**

Find us on:



PKL-11-5719
Reissued 12/11
© 2011 Nordson Corporation
All Rights Reserved.
Printed in U.S.A.
Nordson reserves the right to make design changes between printings.